



Water Blocking Yarn 900D

Type: Water-Blocking Yarn

Composition: Polyester terylene long fiber, Polyacrylate super-absorbent resin

Application: Replacement of filling and flooding compound, Under radial barriers, Water-blocking armoring and between cable components

Property	Unit	Technical Standard
Denier	D	900
Liner Density	m/kg	10,000
Swelling Speed	ml / g / 1min	≥40
Swelling Capacity	ml / g	≥45
Tensile Strength	N	≥15
Elongation at Break	% (min)	≥15
Short Term Stability	°C	230
Long Term Stability	°C	90
Moisture Content	% (max)	≤9

Packaging

ID (mm) : 52 , 76 , 92 , 95, 125 , 127

Tube A -Length: 220mm. Traverse: 200mm. OD: 200-280mm. Weight: 3-5kg

Tube B -Length: 175mm. Traverse: 150mm. OD: 200-280mm. Weight: 2.5-3.5kg

The data presented herein is given in good faith and correct to the best of our knowledge at publication. Values quoted are typical and do not constitute a guarantee of performance and UNIGEL SIBER reserve the right to make alterations without notice. UNIGEL SIBER is a registered trademark

UNIGEL SIBER Inc.
 1027 19th Street S.W
 Hickory,
 NC 28602
 United States of America